


Inch Deep Groove Ball bearings 16 Series



Bearing Number	Dimensions			Basic Load Rating	
	d	D	B	Cr(N)	Cor(N)
1601	4.763 mm	17.463 mm	6.35 mm	600	220
1601 2rs	4.763 mm	17.463 mm	7.938 mm	600	220
1601zz	4.763 mm	17.463 mm	6.35 mm	600	220
1602	6.35 mm	17.463 mm	6.35 mm	635	240
1602 2rs	6.35 mm	17.463 mm	7.938 mm	635	240
1602zz	6.35 mm	17.463 mm	6.35 mm	635	240
1603	7.938 mm	22.225 mm	7.142 mm	745	310
1603 2rs	7.938 mm	22.225 mm	8.733 mm	745	310
1603zz	7.938 mm	22.225 mm	7.142 mm	745	310
1604	9.525 mm	22.225 mm	7.142 mm	750	320
1604 2rs	9.525 mm	22.225 mm	8.733 mm	750	320
1604zz	9.525 mm	22.225 mm	7.142 mm	750	320
1605	7.938 mm	23.017 mm	7.938 mm	745	315
1605 2rs	7.938 mm	23.017 mm	7.938 mm	745	315
1605zz	7.938 mm	23.017 mm	7.938 mm	745	315
1606	9.525 mm	23.017 mm	7.938 mm	750	320
1606 2rs	9.525 mm	23.017 mm	7.938 mm	750	320
1606zz	9.525 mm	23.017 mm	7.938 mm	750	320
1607	11.113 mm	23.017 mm	7.938 mm	1015	430
1607 2rs	11.113 mm	23.017 mm	7.938 mm	1015	430
1607zz	11.113 mm	23.017 mm	7.938 mm	1015	430
1614	9.525 mm	28.575 mm	9.525 mm	1140	520
1614 2rs	9.525 mm	28.575 mm	9.525 mm	1140	520

Inch Deep Groove Ball bearings 16 Series

1614zz	9.525 mm	28.575 mm	9.525 mm	1140	520
1615	11.113 mm	28.575 mm	9.525 mm	1145	530
1615 2rs	11.113 mm	28.575 mm	9.525 mm	1145	530
1615zz	11.113 mm	28.575 mm	9.525 mm	1145	530
1616	12.7 mm	28.575 mm	9.525 mm	1150	450
1616 2rs	12.7 mm	28.575 mm	9.525 mm	1150	450
1616zz	12.7 mm	28.575 mm	9.525 mm	1150	450
1620	11.113 mm	34.925 mm	11.113 mm	1690	800
1620 2rs	11.113 mm	34.925 mm	11.113 mm	1690	800
1620zz	11.113 mm	34.925 mm	11.113 mm	1690	800
1621	12.7 mm	34.925 mm	11.113 mm	1700	815
1621 2rs	12.7 mm	34.925 mm	11.113 mm	1700	815
1621zz	12.7 mm	34.925 mm	11.113 mm	1700	815
1622	14.288 mm	34.925 mm	11.113 mm	1710	825
1622 2rs	14.288 mm	34.925 mm	11.113 mm	1710	825
1622zz	14.288 mm	34.925 mm	11.113 mm	1710	825
1623	15.875 mm	34.925 mm	11.113 mm	1720	835
1623 2rs	15.875 mm	34.925 mm	11.113 mm	1720	835
1623zz	15.875 mm	34.925 mm	11.113 mm	1720	835
1628	15.875 mm	41.275 mm	12.7 mm	2100	1095
1628 2rs	15.875 mm	41.275 mm	12.7 mm	2100	1095
1628zz	15.875 mm	41.275 mm	12.7 mm	2100	1095
1630	19.05 mm	41.275 mm	12.7 mm	2110	1115
1630 2rs	19.05 mm	41.275 mm	12.7 mm	2110	1115
1630zz	19.05 mm	41.275 mm	12.7 mm	2110	1115
1633	15.875 mm	44.45 mm	12.7 mm	2100	1120
1633 2rs	15.875 mm	44.45 mm	12.7 mm	2100	1120
1633zz	15.875 mm	44.45 mm	12.7 mm	2100	1120

Inch Deep Groove Ball bearings 16 Series

1635	19.05 mm	44.45 mm	12.7 mm	2115	1140
1635 2rs	19.05 mm	44.45 mm	12.7 mm	2115	1140
1635zz	19.05 mm	44.45 mm	12.7 mm	2115	1140
1638	19.05 mm	50.8 mm	14.288 mm	2270	1290
1638 2rs	19.05 mm	50.8 mm	14.288 mm	2270	1290
1638zz	19.05 mm	50.8 mm	14.288 mm	2270	1290
1640	22.225 mm	50.8 mm	14.288 mm	2265	1315
1640 2rs	22.225 mm	50.8 mm	14.288 mm	2265	1315
1640zz	22.225 mm	50.8 mm	14.288 mm	2265	1315
1641	25.4 mm	50.8 mm	14.288 mm	2260	1345
1641 2rs	25.4 mm	50.8 mm	14.288 mm	2260	1345
1641zz	25.4 mm	50.8 mm	14.288 mm	2260	1345
1652	28.575 mm	63.5 mm	15.875 mm	3603	2280
1652 2rs	28.575 mm	63.5 mm	15.875 mm	3603	2280
1652zz	28.575 mm	63.5 mm	15.875 mm	3603	2280
1654	31.75 mm	63.5 mm	15.875 mm	3600	2300
1654 2rs	31.75 mm	63.5 mm	15.875 mm	3600	2300
1654zz	31.75 mm	63.5 mm	15.875 mm	3600	2300
1657	31.75 mm	65.088 mm	17.463 mm	4400	2500
1657 2rs	31.75 mm	65.088 mm	17.463 mm	4400	2500
1657zz	31.75 mm	65.088 mm	17.463 mm	4400	2500
1658	33.338 mm	65.088 mm	17.463 mm	4370	2600
1658zz	33.338 mm	65.088 mm	17.463 mm	4370	2600