


Rod Ends For Hydraulic Components



Bearing number	Dimensions/mm													Load ratings/kN		Weight ≈kg
	d	B	dk	C1	d2	h	2	7	d5	d6	e	rs	α°	Dynamic	Static	
SK10E¹)	10	9	16	7	29	24	38.50	15	15	3	2	0.30	12	8.10	15	0.04
SK12E¹)	12	10	18	8	34	27	44	17.50	17.50	3	2	0.30	10	10	21	0.07
SK15ES²)	15	12	22	10	40	31	51	20	21	4	2.50	0.30	8	16	32	0.12
SK16ES²)	16	14	25	11	46	35	58	23	24	4	3	0.30	10	21	40	0.19
SK17ES²)	17	14	25	11	46	35	58	23	24	4	3	0.30	10	21	40	0.18
SK20ES	20	16	29	13	53	38	64.50	27.50	27.50	4	3	0.30	9	30	54	0.26
SK25ES	25	20	35.50	17	64	45	77	33	33.50	4	4	0.60	7	48	72	0.45
SK30ES	30	22	40.70	19	73	51	87.50	37.50	40	4	4	0.60	6	62	95	0.67
SK35ES	35	25	47	21	82	61	102	43	47	4	4	0.60	6	79	125	1.02
SK40ES	40	28	53	23	92	69	115	48	52	4	5	0.60	7	99	156	1.40
SK45ES	45	32	60	27	102	77	128	52	58	6	5	0.60	7	127	208	1.93
SK50ES	50	35	66	30	112	88	144	59	62	6	6	0.60	6	156	250	2.69
SK60ES	60	44	80	38	135	100	167.50	72.50	70	6	8	1	6	245	390	4.60
SK70ES	70	49	92	42	160	115	195	85.50	80	6	10	1	6	313	510	7
SK80ES	80	55	105	47	180	141	231	98	95	6	10	1	6	400	620	11