

Metric Series Taper Roller Bearings



Bearing number	Dimensions/mm					Weight ≈kg	
	d	D	T	B	C		
30202	15	35	11.75	11	10	0.053	
30203	17	40	13.25	12	11	0.079	
30204	20	47	15.25	14	12	0.127	
30205	25	52	16.25	15	13	0.157	
30206	30	62	17.25	16	14	0.238	
30207	35	72	18.25	17	15	0.34	
30208	40	80	19.75	18	16	0.438	
30209	45	85	20.75	19	16	0.488	
30210	50	90	21.75	20	17	0.558	
30211	55	100	22.75	21	18	0.736	
30212	60	110	23.75	22	19	0.93	
30213	65	120	24.75	23	20	1.18	
30214	70	125	26.25	24	21	1.3	
30215	75	130	27.25	25	22	1.43	
30216	80	140	28.25	26	22	1.69	
30217	85	150	30.5	28	24	2.12	
30218	90	160	32.5	30	26	2.6	
30219	95	170	34.5	32	27	3.13	
30220	100	180	37	34	29	3.78	
30221	105	190	39	36	30	4.52	
30222	110	200	41	38	32	5.28	
30224	120	215	43.5	40	34	6.28	
30226	130	230	43.75	40	34	6.83	
30228	140	250	45.75	42	36	8.73	

Metric Series Taper Roller Bearings

30302	15	42	14.25	13	11	0.098	
30303	17	47	15.25	14	12	0.134	
30304	20	52	16.25	15	13	0.172	
30305	25	62	18.25	17	15	0.27	
30306	30	72	20.75	19	16	0.403	
30307	35	80	22.75	21	18	0.538	
30308	40	90	25.25	23	20	0.758	
30309	45	100	27.25	25	22	1.01	
30310	50	110	29.25	27	23	1.28	
30311	55	120	31.5	29	25	1.63	
30312	60	130	33.5	31	26	2.03	
30313	65	140	36	33	28	2.51	
30314	70	150	38	35	30	3.03	
30315	75	160	40	37	31	3.63	
30316	80	170	42.5	39	33	4.24	
30317	85	180	44.5	41	34	5.08	
30318	90	190	46.5	43	36	5.67	
30319	95	200	49.5	45	38	6.55	
30320	100	215	51.5	47	39	7.94	
30321	105	225	53.5	49	41	8.74	
30322	110	240	54.5	50	42	11.4	
32004	20	42	15	15	12	0.097	
32005	25	47	15	15	11.5	0.114	
32006	30	55	17	17	13	0.166	
32007	35	62	18	18	14	0.224	
32008	40	68	19	19	14.5	0.273	
32009	45	75	20	20	15.5	0.346	
32010	50	80	20	20	15.5	0.366	

Metric Series Taper Roller Bearings

32011	55	90	23	23	17.5	0.563	
32012	60	95	23	23	17.5	0.576	
32013	65	100	23	23	17.5	0.63	
32014	70	110	25	25	19	0.848	
32015	75	115	25	25	19	0.909	
32016	80	125	29	29	22	1.6	
32017	85	130	29	29	22	1.35	
32018	90	140	32	32	24	1.79	
32019	95	145	32	32	24	1.83	
32020	100	150	32	32	24	1.91	
32021	105	160	35	35	26	2.4	
32022	110	170	38	38	29	3.02	
32024	120	180	38	38	29	3.18	
32026	130	200	45	45	34	4.94	
32028	140	210	45	45	34	5.15	
32030	150	225	48	48	36	6.25	
32032	160	240	51			7.66	
32203	17	40	17.25	16	14	0.102	
32204	20	47	19.25	18	15	0.163	
32205	25	52	19.25	18	16	0.187	
32206	30	62	21.25	20	17	0.294	
32207	35	72	24.25	23	19	0.461	
32208	40	80	24.75	23	19	0.558	
32209	45	85	24.75	23	19	0.607	
32210	50	90	24.75	23	19	0.648	
32211	55	100	26.75	25	21	0.876	
32212	60	110	29.75	28	24	1.18	
32213	65	120	32.75	31	27	1.58	

Metric Series Taper Roller Bearings

32214	70	125	33.25	31	27	1.68	
32215	75	130	33.25	31	27	1.74	
32216	80	140	35.25	33	28	20.18	
32217	85	150	38.5	36	30	2.75	
32218	90	160	42.5	40	34	3.49	
32219	95	170	45.5	43	37	4.3	
32220	100	180	49	46	39	5.12	
32221	105	190	53	50	43	6.26	
32222	110	200	56	53	46	7.43	
32224	120	215	61.5	58	50	9.6	
32226	130	230	67.75	64	54	11.4	
32228	140	250	71.75	68	58	14.4	
32303	17	47	20.25	19	16	0.174	
32304	20	52	22.25	21	18	0.245	
32305	25	62	25.25	24	20	0.381	
32306	30	72	28.75	27	23	0.592	
32307	35	80	32.75	31	25	0.797	
32308	40	90	35.25	33	27	1.1	
32309	45	100	38.25	36	30	1.46	
32310	50	110	42.25	40	33	1.92	
32311	55	120	45.5	43	35	2.44	
32312	60	130	48.5	46	37	3.02	
32313	65	140	51	48	39	3.66	
32314	70	150	55	51	42	4.46	
32315	75	160	58	55	45	5.35	
32316	80	170	61.5	58	48	6.41	
32317	85	180	63.5	60	49	7.15	
32318	90	190	67.5	64	53	8.57	

Metric Series Taper Roller Bearings

32319	95	200	71.5	67	55	10.1	
32320	100	215	77.5	73	60	12.7	
32321	105	225	81.5	77	63	13.9	
32322	110	240	84.5	80	65	16.6	
31305	25	62	18.25	17	13	0.262	
31306	30	72	20.75	19	14	0.392	
31307	35	80	22.75	21	15	0.514	
31308	40	90	25.25	23	17	0.727	
31309	45	100	27.25	25	18	0.944	
31310	50	110	29.25	27	19	1.21	
31311	55	120	31.5	29	21	1.56	
31312	60	130	33.5	31	22	1.9	
31313	65	140	36	33	23	2.37	
31314	70	150	38	35	25	2.86	
31315	75	160	40	37	26	3.38	
31316	80	170	42.5	39	27	4.05	
31317	85	180	44.5	41	28	4.69	
31318	90	190	46.5	43	30	5.46	
31319	95	200	49.5	45	32	6.46	
31320	100	215	56.5	51	35	8.59	
31321	105	225	58	53	36	9.58	
31322	110	240	63	57	38	12.1	